

NASA-CR-179505-Vol III



National Aeronautics and
Space Administration

(NASA-CR-179505-Vol-3) DETERMINATION OF THE
RELATIVE RESISTANCE TO IGNITION OF SELECTED
TURBOPUMP MATERIALS IN HIGH-PRESSURE,
HIGH-TEMPERATURE, OXYGEN ENVIRONMENTS,
VOLUME 3 Interim Report (NASA) 150 p


N89-16005

Unclas
G3/25 0185105

TEST REPORT

VOLUME III

DETERMINATION OF THE RELATIVE RESISTANCE TO IGNITION
OF SELECTED TURBOPUMP MATERIALS IN
HIGH-PRESSURE, HIGH-TEMPERATURE, OXYGEN ENVIRONMENTS



Lyndon B. Johnson Space Center
White Sands Test Facility
Post Office Drawer MM
Las Cruces, New Mexico 88001
AC 505 524-5011

TEST REPORT
DETERMINATION OF THE RELATIVE RESISTANCE TO IGNITION
OF SELECTED TURBOPUMP MATERIALS IN
HIGH-PRESSURE, HIGH-TEMPERATURE, OXYGEN ENVIRONMENTS

VOLUME III

Issued By
National Aeronautics and Space Administration
Johnson Space Center
White Sands Test Facility
Laboratories Test Office

Prepared By: Joel M. Stoltzfus
Joel M. Stoltzfus, Lockheed-EMSCO

Prepared By: Frank J. Benz
Frank J. Benz/RF
NASA Laboratories Test Office

Approved By: Frank J. Benz for
David L. Phippen, Chief
NASA Laboratories Test Office



ABSTRACT

Advances in the design of the liquid oxygen, liquid hydrogen engines for the Space Transportation System call for the use of warm, high-pressure oxygen as the driving gas in the liquid oxygen turbopump. The NASA Lewis Research Center requested the NASA White Sands Test Facility (WSTF) to design a test program to determine the relative resistance to ignition of nine selected turbopump materials: Hastelloy X, Inconel 600, Invar 36, Monel K-500, Monel 400, nickel 200, silicon carbide, stainless steel 316, and zirconium copper. The materials were subjected to particle impact and to frictional heating in high-pressure oxygen.

In the particle impact tests, nickel 200, Monel 400, and silicon carbide were the most resistant to ignition; Monel K-500 and zirconium copper were slightly less resistant to ignition; and Hastelloy X, Invar 36, and stainless steel 316 were the least resistant to ignition. Inconel 600 was not tested.

In frictional heating tests of pairs of like materials, the ranking was generally upheld, with the materials ranked in order of decreasing resistance to ignition as follows: nickel 200, Inconel 600, Monel 400, Monel K-500, Hastelloy X, Invar 36, and stainless steel 316. Pairs of silicon carbide and zirconium copper failed mechanically at modest contact pressures and did not ignite.

In tests where pairs of different materials were rubbed together, the material rated less resistant to ignition in previous tests appeared to control the resistance to ignition of the pair.

Tests designed to determine the effects of oxygen pressure on the results of frictional heating appeared to indicate that the greater heat rates per unit area required to ignite metals at high pressures resulted from increased convective heat losses from the test samples.

PREFACE

This interim report addresses the test series that resulted from three test plans written at the NASA White Sands Test Facility in response to a request from the NASA Lewis Research Center to determine the relative compatibility of selected turbopump materials in gaseous oxygen. The first test plan, Determination of the Ignition Sensitivity of Selected Turbopump Metals in High Pressure, High Temperature, Oxygen Environments (TP-WSTF-324), proposed tests in which eight materials were impacted with particles in hot, high-pressure oxygen and nine materials were heated frictionally in high-pressure oxygen. The second test plan, TP-WSTF-324 ADDI, proposed tests in which pairs of different materials were rubbed together in high-pressure oxygen to induce frictional heating. The third test plan, Evaluation of Pressure Effects in the WSTF Friction Rubbing Test System (TP-WSTF-356), proposed tests to determine the effects of the test gas pressure on the results of frictional heating tests. Testing proposed in the first and third test plans has been completed, and six of the eight tests proposed in the second test plan have been completed.

TABLE OF CONTENTS

Section	Page
VOLUME I	
LIST OF FIGURES	v
LIST OF TABLES	vii
1.0 INTRODUCTION	1
2.0 OBJECTIVES	2
3.0 PARTICLE IMPACT TESTS	2
3.1 BACKGROUND	3
3.2 TEST SYSTEM DESCRIPTION	4
3.3 TEST CONSIDERATIONS	7
3.3.1 Sample Preparation	
3.3.2 Test Conditions	
3.3.3 Test Procedure	
3.4 PARTICLE IMPACT TEST RESULTS	10
3.4.1 Tests With Impact Plates	
3.4.1.1 Types of Ignition Events Observed	
3.4.1.2 Ignition Susceptibility of the Materials	
3.4.1.3 Discussion of Test Results	
3.4.2 Tests With Rupture Disks	
3.4.2.1 Types of Ignition Events Observed	
3.4.2.2 Ignition Susceptibility of the Materials	
3.4.2.3 Discussion	
4.0 FRICTIONAL HEATING TESTS	19
4.1 BACKGROUND	19
4.2 TEST SYSTEM DESCRIPTION	22
4.3 TEST CONSIDERATIONS	26
4.3.1 Sample Preparation	
4.3.2 Test Conditions	
4.3.3 Test Procedure	
4.4 FRICTIONAL HEATING TEST RESULTS	29
4.4.1 Ignition Resistance of Pairs of Like Materials	
4.4.1.1 General Comments Concerning the Data	
4.4.1.2 Relative Resistance of the Test Materials to Ignition	
4.4.1.3 Discussion of Test Results	
4.4.2 Ignition Resistance of Pairs of Different Materials	
4.4.2.1 General Comments Concerning the Data	
4.4.2.2 Relative Resistance of the Test Materials to Ignition	
4.4.2.3 Discussion of the Test Results	


TABLE OF CONTENTS (Continued)

Section	Page	
4.4.3	Effect of Oxygen Pressure on the Ignition of Materials	
4.4.3.1	General Comments Concerning the Data	
4.4.3.2	Description of the Test Results	
4.4.3.3	Discussion of the Test Results	
5.0	CONCLUSIONS	56
	LIST OF REFERENCES	58
	DISTRIBUTION	60
APPENDIX A:	Temperature Calibration of Particle Impact Tester	A-1
APPENDIX B:	Estimation of Minimum Particle Velocity by a Dent-Block Comparison Test	B-1
VOLUME II		
APPENDIX C:	Data From Particle Impact Test	C-1
APPENDIX D:	Data From Frictional Heating Tests on Pairs of Like Materials	D-1
VOLUME III		
APPENDIX E:	Data From Frictional Heating Tests on Pairs of Different Materials	E-1
VOLUME IV		
APPENDIX F:	Data From Frictional Heating Tests to Determine the Effect of Oxygen Pressure on the Pv Product Required for Ignition	F-1

APPENDIX E

Data From Frictional Heating Tests
on Pairs of Different Materials


TEST NUMBER	TEST MATERIAL		PAGE
	ROTATING SAMPLE	STATIONARY SAMPLE	
252	Monel K-500	Monel K-500	E-1
255			E-9
256			E-17
257	Stainless Steel 316	Zirconium Copper	E-25
258			E-33
259			E-41
260	Stainless Steel 316	Monel K-500	E-49
261			E-57
262			E-65
263	Silicon Carbide	Invar 36	E-73
264			E-81
265			E-89
266	Silicon Carbide	Monel K-500	E-97
267			E-105
268			E-113
272	Monel K-500	Nickel (EP)	E-121
273			E-129
274			E-137




FRT#252: Mon. K500-Stat.; Mon. K500-Rot.

E1

Normal Load (Lbf)




Contains a 5.1 load offset.




FRT#252: Mon. K500-Stat.; Mon. K500-Rot.


Chamber Oxygen Pressure (PSIG)



FRT#252: Mon. K500-Stat.; Mon. K500-Rot.




Sample Wear (Inches)



FRT#252: Mon. K500-Stat.; Mon. K500-Rot.

Torque Load (Lbf)


FRT#252: Mon. K500-Stat.; Mon. K500-Rot.



Time (seconds)

Printed on 4.1 Inad. offset.

Coefficient of Friction




FRT#252: Mon. K500-Stat.; Mon. K500-Rot.

Time (seconds)

Contains a torque load and a normal load offset.

Filtered Coefficient of Friction




FRT#252: Mon. K500-Stat.; Mon. K500-Rot.

Time (seconds)

Contains a torque load and a normal load offset.


Normal Load (Lbf)

FRT#255: Mon. K500-Stat.; Mon. K500-Rot.




Time (seconds)

Contains a +1.7 load offset.




11-3
Chamber Oxygen Pressure (PSIG)



FRT#255: Mon. K500-Stat.; Mon. K500-Rot.


FRT#255: Mon. K500-Stat.; Mon. K500-Rot.

E-12




FRT#255: Mon. K500-Stat.; Mon. K500-Rot.

E-13



FRT#255: Mon. K500-Stat.; Mon. K500-Rot.




Time (seconds)

Torque Load (Lbf)

E-14

Continuation of Load Offset.

Coefficient of Friction




Time (seconds)

FRT#255 : Mon. K500-Stat. ; Mon. K500-Rot.

Contains a torque load and a normal load offset.

Filtered Coefficient of Friction




FRT#255 : Mon. K500-Stat. : Mon. K500-Rot.

Time (seconds)


Containing a torque load and a normal load offset.

FRT#256: Mon. K500-Stat.; Mon. K500-Rot.




FRT#256: Mon. K500-Stat.; Mon. K500-Rot.


E-18




Chamber Oxygen Pressure (PSIG)



FRT#256 : Mon. K500-Stat. ; Mon. K500-Rot.




Sample Wear (Inches)



FRT#256 : Mon. K500-Stat. : Mon. K500-Rot.

Torque Load (Lbf)


FRT#256: Mon. K500-Stat.; Mon. K500-Rot.



Time (seconds)

Contains a -2.6 load offset.

Coefficient of Friction




FRT#256 : Mon. K500-Stat. ; Mon. K500-Rot.

Time (seconds)

Contains a torque load and a normal load offset.

Filtered Coefficient of Friction




FRT#256 : Mon. K500-Stat. ; Mon. K500-Rot.

Time (seconds)

Continuing a torque load and a normal load offset.

FRT#257: ZrCu-Stat.; 316 SS-Rot.




Normal Load (Lbf)


Time (seconds)

Contains a -2.0 load offset.

FRT#257: ZrCu-Stat.; 316 SS-Rot.




Chamber Oxygen Pressure (PSIG)



FRT#257: Zrcu-Stat.; 316 SS-Rot.


FRT#257: ZrCu-Stat.; 316 SS-Rot.



E-28


Sample Wear (Inches)

E-29



FRT#257: ZrCu-Stat.; 316 SS-Rot.

FRT#257: Zrcu-Stat.: 316 SS-Rot.




E-30

ORIGINAL PAGE IS
OF POOR QUALITY

Contains a -3.1 load offset.

Time (seconds)

Coefficient of Friction




Time (seconds)

Contains a torque load and a normal load offset.

FRT#257: Zncu-Stat.: 316 SS-Rot.

Filtered Coefficient of Friction




FRT#257: ZrCu-Stat.; 316 SS-Rot.

Time (seconds)

contains a torque load and a normal load offset.

FRT#258: ZrCu-Stat.; 316 SS-Rot.




(+ 07) DEPT [REDACTED]

Time (seconds)

Contains a -1.2 load offset.


FRT#258: ZrCu-Stat.; 316 SS-Rot.




E-34

ORIGINAL PAGE IS
OF POOR QUALITY

FRT#258: ZrCu-Stat.; 316 SS-Rot.




FRT#258: ZrCu-Stat.; 316 SS-Rot.




FRT#258: ZrCu-Stat.; 316 SS-Rot.

E-37
Sample Wear (Inches)



Time (seconds)

FRT#258: ZrCu-Stat.; 316 SS-Rot.



E-38


ORIGINAL PAGE IS
OF POOR QUALITY

Contains a -3.4 load offset.

FRT#258: ZrCu-Stat.; 316 SS-Rot.

Coefficient of Friction

E-39




Time (seconds)

Contains a torque load and a normal load offset.

ALWAYS ROTATE IN THE DIRECTION OF THE ARROW

FRT#258: ZrCu-Stat.; 316 SS-Rot.



Time (seconds)

contains a torque load and a normal load offset.


NOISE TO SUBSTITUTION OF FRICTION

E-40

ORIGINAL PAGE IS
OF POOR QUALITY


FRT#259: ZrCu-Stat.; 316 SS-Rot.

ORIGINAL PAGE IS
OF POOR QUALITY



(497) PROF LEWJON

FRT#259 : Zrcu-Stat. : 316 SS-Rot.




E-42


ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
OF POOR QUALITY


FRT#259: ZrCu-Stat.; 316 SS-Rot.



FRT#259: ZrCu-Stat.; 316 SS-Rot.




FRT#259: Zrcu-Stat.: 316 SS-Rot.



Sample Number (Inches)

E-45

FRT#259: ZrCu-Stat.: 316 SS-Rot.




Time (seconds)

Torque Load (Lbf)

E-46

Contains a -3.2 load offset.

FRT#259: ZrCu-Stat.; 316 SS-Rot.




ORIGINAL PAGE IS
OF POOR QUALITY

Contains a torque load and a normal load offset.

Filtered Coefficient of Friction

E-48

ORIGINAL PAGE IS
OF POOR QUALITY




FRT#259: ZrCu-Stat.; 316 SS-Rot.

Contains a torque load and a normal load offset.

FRT#260: Mon. K500-Stat.; 316 SS-Rot.


ORIGINAL PAGE IS
OF POOR QUALITY



E-49

Contains a -12.3 load offset.

FRT#260: Mon. K500-Stat.: 316 SS-Rot.




E-50

ORIGINAL PAGE IS
OF POOR QUALITY


FRT#260: Mon. K500-Stat.; 316 SS-Rot.

E-51
Chamber Oxygen Pressure (PSIG)



Time (seconds)


FRT#260: Mon. K500-Stat.; 316 SS-Rot.




E-52

ORIGINAL PAGE IS
OF POOR QUALITY

FRT#260: Mon. K500-Stat.; 316 SS-Rot.



Time (seconds)




Torque Load (Lbf)

E-54

FRT#260: Mon. K500-Stat.: 316 SS-Rot.

Coefficient of Friction

FRT#250: Mon. K500-Stat.; 316 SS-Rot.




ORIGINAL PAGE IS
OF POOR QUALITY

Contains a torque load and a normal load offset.


Filtered Coefficient of Friction

FRT#260: Mon. K500-Stat.; 316 SS-Rot.




Contains a torque load and a normal load offset.

FRT#261: Mon. K500-Stat.; 316 SS-Rot.




Contains a -0.5 load offset.

FRT#261: Mon. K500-Stat.; 316 SS-Rot.




FRT#261: Mon. K500-Stat.; 316 SS-Rot.

E-59
Chamber Oxygen Pressure (PSIG)



Time (seconds)

Temperature (°F)




FRT#261: Mon. K500-Stat.; 316 SS-Rot.

Time (seconds)


Sample Wear (Inches)

E-61



FRT#261: Mon. K500-Stat.; 316 SS-Rot.

FRT#261: Mon. K500-Stat.; 316 SS-Rot.




E-62

ORIGINAL PAGE IS
OF POOR QUALITY

Contains a +.7 load offset.

ORIGINAL PAGE IS
OF POOR QUALITY



FRT#261: Mon. K500-Stat.; 316 SS-Rot.


Time (seconds)

Contains a torque load and a normal load offset.

Coefficient of Friction

Filtered Coefficient of Friction

E-64




FRT#261; Mon. K500-Stat.; 316 SS-Rot.

Contains a torque load and a normal load offset.

Time (seconds)

Normal Load (Lbf)




FRT#262 : Mon. K500-Stat. : 316 SS-Rot.

Positive = -2.0 load offset.


Time (seconds)

FRT#262: Mon. K500-Stat.; 316 SS-Rot.

99-E



Chamber Oxygen Pressure (PSIG)




FRT#262: Mon. K500-Stat.; 316 SS-Rot.

ORIGINAL PAGE IS
OF POOR QUALITY


Time (seconds)

FRT#262: Mon. K500-Stat.; 316 SS-Rot.



Sample Wear (Inches)


E-69



FRT#262 : Mon. K500-Stat. ; 316 SS-Rot.

E-70

Torque Load (Lbf)




FRT#262: Mon. K500-Stat.: 316 SS-Rot.

Contains a +.8 load offset.

Time (seconds)

FRT#262 : Mon. K500-Stat. ; 316 SS-Rot.



Time (seconds)

90
80
70
60
50
40
30
20
10
0


Coefficient of Friction

E-71

ORIGINAL PAGE IS
OF POOR QUALITY

Contains a torque load and a normal load offset.


Filtered Coefficient of Friction



FRT#262: Mon. K500-Stat.: 316 SS-Rot.


Contains a torque load and a normal load offset.

FRT#263: INVAR-36-Stat.: SIC-Rot.



Contains a -12.7 load offset.


FRT#263: INVRR-36-St at. ; SIC-Rot.




E-74

ORIGINAL PAGE IS
OF POOR QUALITY


FRT#263: INVAR-36-Stat.; SiC-Rot.



FRT#263: INVAR-36-Stat.; SiC-Rot.




FRT#263: INVRR-36-Stat.; SIC-Rot.



Time (seconds)

Sample Wear (Inches)

FRT#263: INVAR-36-Stat.; SIC-Rot.



E-78


ORIGINAL PAGE IS
OF POOR QUALITY

Contains a +.5 load offset.

Time (seconds)

Contains a torque load and a normal load offset.

Time (seconds)




ORIGINAL PAGE IS
OF POOR QUALITY

FRT#263 : INVRR-36-Stat. ; SIC-Rot.

FRT#263: INVAR-36-Stat.; SiC-Rot.

E-80


Filtered Coefficient of Friction



Time (seconds)

Contains a torque load and a normal load offset.

FRT#264: INVRR-36-Stat.: SIC-Rot.



Time (seconds)


Continues a -5.4 load offset.

Normal Load (Lbf)


E-81

ORIGINAL PAGE IS
OF POOR QUALITY

FRT#264: INVAR-36-Stat.; SiC-Rot.




Chamber Oxygen Pressure (PSIG)




FRT#264: INVRR-36-St at. : SIC-Rot.

FRT#264: INVRR-36-5t at. ; SIC-Rot.




E-84

FRT#264: INVAR-36-Stat.; SiC-Rot.



FRT#264 : INVAR-36-Stat. : SIC-Rot.



E-86


Torque Load (Lbf)

ORIGINAL PAGE IS
OF POOR QUALITY

Contains a +2.9 load offset.

Time (seconds)

ORIGINAL PAGE IS
OF POOR QUALITY



FRT#264: INVRR-36-Stat.; SIC-Rot.

Contains a torque load and a normal load offset.


Time (seconds)

Coefficient of Friction

E-87

FRT#264: INVAR-36-Stat.; SiC-Rot.


Filtered Coefficient of Friction



Time (seconds)


Contains a torque load and a normal load offset.

FRT#265: INVAR-36-Stat.; SiC-Rot.




Contains a -10.7 load offset.

FRT#265: INVRR-36-St at. ; SIC-Rot.




ORIGINAL PAGE IS
OF POOR QUALITY

FRT#265: INVAR-36-Stat.; SiC-Rot.




C-2

FRT#265: INVAR-36-Stat.; SiC-Rot.



Sample Wear (Inches)


E-93



FRT#265: INVWR-36-St at. : SIC-Rot.

Time (seconds)

FRT#265: INVRR-36-Stat.; SIC-Rot.



Time (seconds)


Torque Load (Lbf)

E-94

ORIGINAL PAGE IS
OF POOR QUALITY

Contains a +1.5 load offset.

Coefficient of Friction



Time (seconds)


Constant torque and a normal load offset.

FRT#265: INVR-36-Stat.; SIC-Rot.

ORIGINAL PAGE IS
OF POOR QUALITY

Filtered Coefficient of Friction


E-96 ORIGINAL PAGE IS OF POOR QUALITY




FRT#265; INVRR-36-Stat.; SIC-Rot.

Contains a torque load and a normal load offset.


FRT#266: Mon. K500-Stat.; SiC-Rot.





FRT#266: Mon. K500-Stat.: SIC-Rot.

Chamber Oxygen Pressure (PSIG)




FRT#266: Mon. K500-Stat.: SIC-Rot.

ORIGINAL PAGE IS
OF POOR QUALITY

FRT#266: Mon, K500-Stat.: SIC-Rot.


E-100



Sample Wear (Inches)

E-101

Time (seconds)




ORIGINAL PAGE IS
OF POOR QUALITY

FRT#266: Mon. K500-Stat.: SIC-Rot.

FRT#266: Mon. K500-Stat.; SiC-Rot.

Torque Load (Lbf)




E-102

ORIGINAL PAGE IS
OF POOR QUALITY

Contains a +3.6 load offset.

Time (seconds)

ORIGINAL PAGE IS
OF POOR QUALITY



FRT#266 : Mon. K500-Stat. : SIC-Rot.


Time (seconds)

Contains a torque load and a normal load offset.

Coefficient of Friction

E-104

Filtered Coefficient of Friction




FRT#266 : Mon. K500-Stat. : SIC-Rot.

Time (seconds)

Filtering a torque load and a normal load offset

FRT#267: Mon. K500-Stat.; SIC-Rot.

ORIGINAL PAGE IS
OF POOR QUALITY




Time (seconds)

Normal Load (Lbf)

E-105


Load-time = 1.7 load offset.

FRT#267: Mon. K500-Stat.; SIC-Rot.




901-3
ORIGINAL PAGE IS
OF POOR QUALITY

FRT#267: Mon. K500-Stat.; SiC-Rot.



FRT#267: Mon. K500-Stat.; SiC-Rot.




Time (seconds)

Temperature (°F)

Sample Wear (Inches)


601-3



FRT#267: Mon. K500-Stat.; SIC-Rot.

Time (seconds)

FRT#267: Mon. K500-Stat.: SIC-Rot.



Time (seconds)


Torque Load (Lbf)

E-110

ORIGINAL PAGE IS
OF POOR QUALITY


Contains a 48.7 load offset.

FRT#267: Mon. K500-Stat.; SiC-Rot.



Contains a torque load and a normal load offset.

Filtered Coefficient of Friction




FRT#267; Mon. K500-Stat.; SIC-Rot.


Time (seconds)

... a normal load and a normal load offset.


FRT#268: Mon. K500-Stat.; SiC-Rot.




FRT#268: Mon. K500-Stat.; SiC-Rot.



FRT#268: Mon. K500-Stat.; SiC-Rot.




FRT#268: Mon. K500-Stat.; SIC-Rot.



FRT#268 : Mon. K500-Stat. ; SIC-Rot.

ORIGINAL PAGE IS
OF POOR QUALITY



Sample Wear (Inches)

E-117


Time (seconds)

FRT#268: Mon. K500-Stat.; SiC-Rot.

(f97) reo7 anbuoL


E-118

ORIGINAL PAGE IS
OF POOR
QUALITY



Contains a +6.5 load offset.

Coefficient of Friction



Time (seconds)


Contains a torque load and a normal load offset.

FRT#268 : Mon. K500-Stat. : SIC-Rot.

ORIGINAL PAGE IS
OF POOR QUALITY

FRT#268: Mon. K500-Stat.; SiC-Rot.

Filtered Coefficient of Friction
E-120




Time (seconds)

Contains a torque load and a normal load offset.

Normal Load (Lbf)


FRT#272: E1eCP1Ni-Stat.; Mon. K500-Rot.




ORIGINAL PAGE IS
OF POOR QUALITY

7 E 1-1-1 -01-1-1

FRT#272: E1ecP1N1-Stat.; Mon. K500-Rot.




Chamber Oxygen Pressure (PSIG)



FRT#272: E1ecP1N1-St at. ; Mon. K500-Rot.

FRT#272: ElecP1Ni-Stat.; Mon. K500-Rot.




E-124

ORIGINAL PAGE IS
OF POOR
QUALITY


FRT#272: ElecPINi-Stat.; Mon. K500-Rot.

E-125

Sample Wear (Inches)



FRT#272: E1ecP1N1-Stat.; Mon. K500-Rot.



Time (seconds)

Torque Load (Lbf)


E-126

ORIGINAL PAGE IS
OF POOR QUALITY

Positive = -24.9 load offset.

Coefficient of Friction

E-127 ORIGINAL POSITION OF POOR QUALITY




FRT#272: E1ecP1N1-Stat.; Mon. K500-Rot.

Time (seconds)

Contains a torque load and a normal load offset.

FRT#272: ElecP1Ni-Stat.; Mon. K500-Rot.


Filtered Coefficient of Friction



E-128

Contains a torque load and a normal load offset.


FRT#273: ElecP1Ni-Stat.; Mon. K500-Rot.



Normal Load (Lbf)


Time (seconds)

FRT#273: ElecP1Ni-Stat.; Mon. K500-Rot.




FRT#273: ElecP1Ni-Stat.; Mon. K500-Rot.

E-131
Chamber Oxygen Pressure (PSIG)



Time (seconds)

FRT#273: E1ecP1N1-Stat.: Mon. K500-Rot.



Time (seconds)


Temperature (°F)

ORIGINAL PAGE IS
OF POOR QUALITY

E-132


FRT#273: ElecP1Ni-Stat.; Mon. K500-Rot.

E-133
Sample Wear (Inches)



Time (seconds)

FRT#273: E1ecP1N1-Stat.; Mon. K500-Rot.



E-134

(197) 007 anbol Torque Load


ORIGINAL PAGE IS
OF POOR QUALITY

Contains a -27.1 load offset.

Time (seconds)

70 60 50 40 30 20 10 0 -10

ORIGINAL PAGE IS
OF POOR QUALITY



FRT#273: E1ecP1N1-Stat.: Mon. K500-Rot.


Time (seconds)

Contains a torque load and a normal load offset.

Coefficient of Friction

E-135

FRT#273: ElecP1Ni-Stat.; Mon. K500-Rot.



Time (seconds)


Filtered Coefficient of Friction

E-136


ORIGINAL PAGE IS
OF POOR QUALITY

Restoring a torque load and a normal load offset.


FRT#274: ElecP1Ni-Stat.; Mon. K500-Rot.



FRT#274: ElecP1Ni-Stat.; Mon. K500-Rot.




FRT#274: ElecP1Ni-Stat.; Mon. K500-Rot.



Sample Wear (Inches)


E-141



FRT#274: ElecP1N1-Stat.; Mon. K500-Rot.

FRT#274: ElecP1Ni-Stat.; Mon. K500-Rot.

E-142
Torque Load (Lbf)




Contains a -20.0 load offset.

FRT#274: ElecP1Ni-Stat.; Mon. K500-Rot.

E-143

Coefficient of Friction



Time (seconds)

contains a torque load and a normal load offset.


ORIGINAL PAGE IS
OF POOR QUALITY

Filtered Coefficient of Friction

E-144

Contains a torque load and a normal load offset.

Time (seconds)



FRT#274: E1ecP1N1-Stat.: Mon. K500-Rot.